



SPEAKERS  
MAXX

# MAXX 12A SUB

[Back](#)

- Hi-Res
- Manual



**POWER**  
 600W PROGRAM  
**TRANSDUCER LOW**  
 12" Woofer, 2,5" Voice Coil with Ventilation  
**MAX SPL**  
 123,8dB

Model	MAXX 12A SUB
System Type	Active Subwoofer Speaker Cabinet
Transducer Low	12" woofer - 2.5" voice coil with ventilation
Frequency Response	47Hz-125Hz (-6dB)
Active Crossover:	HPF 80Hz under analog processor
Max SPL	96dB / 123.8dB Max
Power Rating	600W PROGRAM / 1200W PEAK
Input Connector	L-R (COMBO / XLR-F) / L-R Link (2 - XLR - M) / L-R Output (2 - XLR - M) Balanced (15k Ohms)
Input Level:	L-R Line Input 0dBu
External Controls	Volume Control / Power on with Green LED / Clip Limiter with RED LED / Ground Lift / Phase Switch / HPF 100Hz Bypass
Power Supply	110-120V / 220-240V 50/60Hz
Enclosure Construction	Painted Plywood cabinet / Black Metal Grille Protection / Rubber feet
Dimensions (HxWxD)	62.9 x 57.9 x 47.4
Weight (kg)	24

[Back](#)



## Topp Pro Professional Audio Gear

Worldwide Distribution Contact  
 No.1, Lane 17, Sec. 2, Hanshi W. Road  
 Taichung, Taiwan  
 Ph. +886-4-22313737 ext. 7122  
 Fax. +886-4-22346757